



MATERIAL SAFETY DATA SHEET
Bromophenol Blue Indicator Solution

Section 1 - Chemical Product and Company Identification

MSDS Name: Bromophenol Blue Indicator Solution
Catalog Numbers: B/4630/46, B/4630L/05, B/4630L/08
Synonyms: None.
Company Identification: Fisher Scientific UK
 Bishop Meadow Road, Loughborough
 Leics. LE11 5RG
For information in Europe, call: (01509) 231166
Emergency Number, Europe: 01509 231166

Section 2 - Composition, Information on Ingredients

| CAS# | Chemical Name: | % | EINECS# | Hazard Symbols: | Risk Phrases: |
|----------|-----------------|--------|-----------|-----------------|---------------|
| 64-17-5 | Ethyl alcohol | >99 % | 200-578-6 | F | 11 |
| 115-39-9 | Bromphenol blue | <1.0 % | 204-086-2 | | |

Text for R-phrases: see Section 16

Hazard Symbols: F



Risk Phrases: 11

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Highly flammable.

Potential Health Effects

- Eye:** Causes severe eye irritation. May cause painful sensitization to light. May cause chemical conjunctivitis and corneal damage.
- Skin:** Causes moderate skin irritation. May cause cyanosis of the extremities.
- Ingestion:** May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause systemic toxicity with acidosis. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.
- Inhalation:** Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. Causes respiratory tract irritation. May cause narcotic effects in high concentration. Vapors may cause dizziness or suffocation.
- Chronic:** May cause reproductive and fetal effects. Laboratory experiments have resulted in mutagenic effects. Animal studies have reported the development of tumors. Prolonged exposure may cause liver, kidney, and heart damage.

Section 4 - First Aid Measures

| | |
|----------------------------|--|
| Eyes: | Get medical aid. Gently lift eyelids and flush continuously with water. |
| Skin: | Get medical aid. Wash clothing before reuse. Flush skin with plenty of soap and water. |
| Ingestion: | Do not induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. Get medical aid. |
| Inhalation: | Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation. |
| Notes to Physician: | Treat symptomatically and supportively. Persons with skin or eye disorders or liver, kidney, chronic respiratory diseases, or central and peripheral nervous system diseases may be at increased risk from exposure to this substance. |
| Antidote: | Replace fluid and electrolytes. |

Section 5 - Fire Fighting Measures

| | |
|-----------------------------|--|
| General Information: | Replace fluid and electrolytes. As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors may form an explosive mixture with air. Vapors can travel to a source of ignition and flash back. Will burn if involved in a fire. Flammable Liquid. Can release vapors that form explosive mixtures at temperatures above the flashpoint. Use water spray to keep fire-exposed containers cool. Containers may explode in the heat of a fire. |
| Extinguishing Media: | For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam. For large fires, use water spray, fog, or alcohol-resistant foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do NOT use straight streams of water. |

Section 6 - Accidental Release Measures

| | |
|-----------------------------|---|
| General Information: | Use proper personal protective equipment as indicated in Section 8. |
| Spills/Leaks: | Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Remove all sources of ignition. Use a spark-proof tool. Provide ventilation. A vapor suppressing foam may be used to reduce vapors. |

Section 7 - Handling and Storage

| | |
|------------------|--|
| Handling: | Wash thoroughly after handling. Use only in a well-ventilated area. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep container tightly closed. Keep away from heat, sparks and flame. Avoid ingestion and inhalation. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. |
| Storage: | Keep away from heat, sparks, and flame. Keep away from sources of ignition. Store in a tightly closed container. Keep from contact with oxidizing materials. Store in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area. Do not store near perchlorates, peroxides, chromic acid or nitric acid. |

Section 8 - Exposure Controls, Personal Protection

Engineering Controls:

Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Exposure Limits

CAS# 64-17-5:

United Kingdom, WEL - TWA: 1000 ppm TWA; 1920 mg/m³ TWA United Kingdom, WEL - STEL: 3000 ppm STEL; 5760 mg/m³ STEL

United States OSHA: 1000 ppm TWA; 1900 mg/m³ TWA

Belgium - TWA: 1000 ppm TWA; 1907 mg/m³ TWA

France - VME: 1000 ppm VME; 1900 mg/m³ VME France - VLE: 5000 ppm VLCT;

9500 mg/m³ VLCT

Germany: 500 ppm TWA (exposure factor 2); 960 mg/m³ TWA (exposure factor 2)

Malaysia: 1000 ppm TWA; 1880 mg/m³ TWA

Netherlands: 500 ppm MAC; 1000 mg/m³ MAC

Russia: 1000 mg/m³ TWA (vapor) Russia: 2000 mg/m³ STEL (vapor)

Spain: 1000 ppm VLA-ED; 1910 mg/m³ VLA-ED

CAS# 115-39-9:

Personal Protective Equipment

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin: Wear appropriate protective gloves to prevent skin exposure.

Clothing: Wear appropriate protective clothing to prevent skin exposure.

Respirators: A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use.

Section 9 - Physical and Chemical Properties

Physical State: Liquid

Color: blue

Odor: Alcohol-like.

pH: Not available

Vapor Pressure: Not available

Viscosity: Not available

Boiling Point: Not available

Freezing/Melting Point: Not available

Autoignition Temperature: Not applicable

Flash Point: 13 deg C (55.40 deg F)

Explosion Limits: Lower: Not available

Explosion Limits: Upper: Not available

Decomposition Temperature: Not available

Solubility in water: Miscible

Specific Gravity/Density: Not available.

Molecular Formula: Solution

Molecular Weight: 0

Section 10 - Stability and Reactivity

Chemical Stability: Stable under normal temperatures and pressures.

Conditions to Avoid: Incompatible materials, ignition sources, excess heat, oxidizers.

Incompatibilities with Other Materials Strong oxidizing agents, acids, alkali metals, ammonia, hydrazine, peroxides, sodium, acid anhydrides, calcium hypochlorite, chromyl chloride, nitrosyl perchlorate, bromine pentafluoride, perchloric acid, silver nitrate, mercuric nitrate, potassium tert-butoxide, magnesium perchlorate, acid chlorides, platinum, uranium hexafluoride, silver oxide, iodine heptafluoride, acetyl bromide, disulfuryl difluoride, tetrachlorosilane + water, acetyl chloride, permanganic acid, ruthenium (VIII) oxide, uranyl perchlorate, potassium dioxide.

Hazardous Decomposition Carbon monoxide, irritating and toxic fumes and gases, carbon dioxide.

Products

Hazardous Polymerization

Has not been reported.

Section 11 - Toxicological Information

RTECS#: CAS# 64-17-5: KQ6300000
CAS# 115-39-9: SJ7453000

LD50/LC50: RTECS:
CAS# 64-17-5: Draize test, rabbit, eye: 500 mg Severe;
Draize test, rabbit, eye: 500 mg/24H Mild;
Draize test, rabbit, skin: 20 mg/24H Moderate;
Inhalation, mouse: LC50 = 39 gm/m³/4H;
Inhalation, rat: LC50 = 20000 ppm/10H;
Oral, mouse: LD50 = 3450 mg/kg;
Oral, rabbit: LD50 = 6300 mg/kg;
Oral, rat: LD50 = 7060 mg/kg;
Oral, rat: LD50 = 9000 mg/kg;
.
RTECS:
CAS# 115-39-9:

Carcinogenicity: Ethyl alcohol - Not listed as a carcinogen by ACGIH, IARC, NTP, or CA Prop 65.
Bromphenol blue - Not listed as a carcinogen by ACGIH, IARC, NTP, or CA Prop 65.

Other: Standard Draize Test(Skin, rabbit) = 20 mg/24H (Moderate) Standard Draize Test:
Administration into the eye (rabbit) = 500 mg (Severe).

Section 12 - Ecological Information

Ecotoxicity: Fish: Rainbow trout: LC50 = 12900-15300 mg/L; 96 Hr; Flow-through @ 24-24.3°C
Fish: Rainbow trout: LC50 = 11200 mg/L; 24 Hr; Fingerling (Unspecified)
Bacteria: Phytobacterium phosphoreum: EC50 = 34900 mg/L; 5-30 min; Microtox test

Section 13 - Disposal Considerations

Products considered hazardous for supply are classified as Special Waste and the disposal of such chemicals is covered by regulations which may vary according to location. Contact a specialist disposal company or the local authority or advice. Empty containers must be decontaminated before returning for recycling.

Section 14 - Transport Information

| | IATA | IMO | RID/ADR |
|-----------------------|------------------|------------------|------------------|
| Shipping Name: | Ethanol solution | ETHANOL SOLUTION | ETHANOL SOLUTION |
| Hazard Class: | 3 | 3 | 3 |
| UN Number: | 1170 | 1170 | 1170 |
| Packing Group: | III | III | II |

Section 15 - Regulatory Information

European/International Regulations

European Labeling in Accordance with EC Directives

Hazard Symbols: F

Risk Phrases:

R 11 Highly flammable.

Safety Phrases:

S 7 Keep container tightly closed.

S 16 Keep away from sources of ignition - No smoking.

WGK (Water Danger/Protection)

CAS# 64-17-5: 0

CAS# 115-39-9: Not available

Canada

CAS# 64-17-5 is listed on Canada's DSL List

CAS# 115-39-9 is listed on Canada's DSL List

US Federal

TSCA

CAS# 64-17-5 is listed on the TSCA Inventory.

CAS# 115-39-9 is listed on the TSCA Inventory.

Section 16 - Other Information

Text for R-phrases from Section 2

R 11 Highly flammable.

MSDS Creation Date: 4/17/1998

Revision #8 Date 8/10/2007

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages howsoever arising, even if the company has been advised of the possibility of such damages.
